

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

DEFINOX - DPX AND DPAX

DE-AD150011100 DPX Butterfly valve SS-UH DN 150

- · Reliable and economical technology
- · Quick installation and removal
- · Can be used anywhere, many different types of gaskets
- Low pressure drop
- Product flow without media retention



IIIII.....

PRODUCT DESCRIPTION

We offer high quality butterfly valves that meet the strongest requirements of process technology, and are the ideal solution for food, brewery, cosmetic and pharmaceutical processes.

Technical advantages of DPX & DPAX butterfly valves:

- · From DN 25 to DN 150
- · Numerous end connections available: SMS DIN Clamp Between flange

Different Operating Systems:

- · Stainless steel handle (right or left closing)
- · Multi-position handle (right or left closing)
- · Easy adjustment handle
- · Micrometric adjustment handle
- · Normally open "NO", Normally closed "NC" or Double effect "DE" pneumatic actuator

Product benefits:

- · Reliable and economical technology
- · Quick installation and removal
- · Large range of gaskets allow this valve to be used anywhere
- · Low pressure drop
- · Product flow without media retention

With the option of: (to be ordered separately)

- · Mounting of pneumatic actuator
- · Mounting the control top for controlling the valve
- · Mounting of handles in div. editions.

TECHNICAL DATA

Certificate	3.1 EN 10204
Connection type	Weld ends
Description	Butterfly valve without handle
Design norm	DIN 11851

Housing	Aisi 316L
Housing	EPDM
Inner diameter	150 mm
Material disc sealing	EPDM
Operating pressure max	8 bar
Outer diameter	154 mm
Surface finish	0,8/1,2µm
Temperature range	0°C/120°C
Weight	5.6 kg



