**OEM Automatic Ltd**
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# DEFINOX - SAMPLING VALVE - 6/8 - PEX - PEAX

Manual and pneumatic

DE-PD006A51100
Sampling Valve PEAX, Clamp, Pneumatic, 6/8, VMQ




- Simple and safe solution for sampling
- 3.1 EN10204 - EHEDG
- SIP or CIP
- Compact pneumatic actuator
- Fast and easy membrane replacement

**PRODUCT DESCRIPTION**

**PEX Test outlet valve**

Specifications:
- DN 6/8

Materials:
- Body: stainless steel 1.4404 / 316L machined from solid item
- Handle: white plastic or stainless steel 1.4301 / 304
- Membrane: FKM (black / green with spot) - WMQ (white) - EPDM (black) - PFA / EPDM (white - hard)

Connections:
- Welding on tank
- Clamp
- Welding on pipes
- Exterior thread

Controls:
- Manual - PEX - Ergonomic handle
- Pneumatic

Surface:
- RA exterior = 0.8 µm
- RA inside = 0.8 µm standard (0.4 µm on request)


Operating conditions:
- Max. temperature: + 120 ° C
- Min. temperature: 0 ° C
- Max. working pressure: 10 bar


ACS Control Top
Definox LED Controllers allow you to monitor and control your valves from a central monitoring system and provide real-time warnings for any malfunctioning conditions so that immediate action can be taken and production stops can be minimized. The Definox LED Controller is configurable bar and user-friendly and offers a host of features.


# TECHNICAL DATA

| | |
|---|---|
| **Certificate** | 3.1 EN10204 |


| | |
|---|---|
| **Connection type** | Clamp |
| **Description** | Pneumatic |
| **Housing** | Aisi 316L / 1.4404 |
| **Housing** | VMQ |
| **Inner diameter** | 4.5 mm |
| **Process connection** | 1 x 6/8 pipe |
| **Surface finish** | RA<0,8/1,2µm |










**Clamp Ø 50,4**




**Clamp Ø 50,4**






Indsvejsning på tank Clamp tilslutning Indsvejsning på rør Gevind tilslutning