OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

DEFINOX - SAMPLING VALVE - 10/12 PEX - PEAX

Manual and pneumatic

DE-PD010J66100
Sampling Valve PEX, Clamp, Manual SS Handle, 10/12, White EPDM



- SIP or CIP
- Simple and safe solution for sampling
- Compact pneumatic actuator
- Fast and easy membrane replacement
- 3.1 EN10204 - EHEDG

PRODUCT DESCRIPTION

PEX Sampling Valve

Specifications:
- DN 10/12

Materials:
- Body: stainless steel 1.4404 / 316L machined from solid item
- Handle: white plastic or stainless steel 1.4301 / 304
- Membrane: FKM (black / green with spot) - WMQ (white) - EPDM (black) - PFA / EPDM (white - hard)

Connections:
- Welding on tank
- Clamp
- Welding on pipes
- Exterior thread

Controls:
- Manual - PEX - Ergonomic handle
- Pneumatic

Surface:
- RA exterior = 0.8 µm
- RA inside = 0.8 µm standard (0.4 µm on request)


Operating conditions:
- Max. temperature: + 120 ° C
- Min. temperature: 0 ° C
- Max. working pressure: 10 bar


ACS Control Top
Definox LED Controllers allow you to monitor and control your valves from a central monitoring system and provide real-time warnings for any malfunctioning conditions so that immediate action can be taken and production stops can be minimized. The Definox LED Controller is configurable bar and user-friendly and offers a host of features.


TECHNICAL DATA

Certificate	3.1 EN10204


Connection type	Clamp
Description	Manual stainless steel handle
Housing	Aisi 316L / 1.4404
Housing	White EPDM
Inner diameter	8 mm
Process connection	2 x 10/12 pipes
Surface finish	RA<0,8/1,2µm










Clamp Ø 50,4







Clamp Ø 50,4





Indsvejsning på tank Clamp tilslutning Indsvejsning på rør Gevind tilslutning