




DEFINOX - CHECK VALVE WITH CLAMP ENDS

DE-UU063A11100-R55
Check valve, 2½", PFA/EPDM

- Designed for a minimal pressure drop
- Vertical mounting for an improved seal
- Quick and easy installation
- Connection: Clamp
- Sealing types: PFA - FKM - EPDM - PTFE



PRODUCT DESCRIPTION

Our products are of high quality and design that meet the strongest requirements of process technology and are the ideal solution for Food, Brewery, Cosmetics and Pharmaceutical processes!

Technical Advantages:

- 1/2" - DN 125
- Interior surface roughness Ra = 0.8 µm
- Vertical mounting for an improved seal and eliminate retention
- Fast and easy disassembly
- Connection: Welding ends
- Multiple packing types: PFA - FKM - EPDM.
- Approvals : 3A - ATEX - DESP - 3.1 - 2.1 - E1935 / 2004 - CE - REACH - ANIA

TECHNICAL DATA

Certificate	3.1 EN10204
Connection type	Clamp ends
Description	Plug with FKM
Design norm	SMS
Flange	Ø77.5mm
Housing	PFA/EPDM
Inner diameter	60.3 mm
Material quality	1.4404
Operating pressure max	10 bar
Outer diameter	63.5 mm
Output	90 Mbar
Surface finish	RA<0,8/1,2µm

Temperature operational max	120 °C
Temperature operational min	0 °C
Weight	2.6 kg