




## DEFINOX - CHECK VALVE WITH CLAMP ENDS

DE-UU019A13100-R55  
Check valve, 3/4", PFA/PTFE

- Designed for a minimal pressure drop
- Vertical mounting for an improved seal
- Quick and easy installation
- Connection: Clamp
- Sealing types: PFA - FKM - EPDM - PTFE



### PRODUCT DESCRIPTION

Our products are of high quality and design that meet the strongest requirements of process technology and are the ideal solution for Food, Brewery, Cosmetics and Pharmaceutical processes!

Technical Advantages:

- 1/2" - DN 125
- Interior surface roughness  $R_a = 0.8 \mu m$
- Vertical mounting for an improved seal and eliminate retention
- Fast and easy disassembly
- Connection: Welding ends
- Multiple packing types: PFA - FKM - EPDM.
- Approvals : 3A - ATEX - DESP - 3.1 - 2.1 - E1935 / 2004 - CE - REACH - ANIA

### TECHNICAL DATA

Certificate	3.1 EN10204
Connection type	Clamp ends
Design norm	SMS
Flange	Ø25.4mm
Housing	PFA/PTFE
Inner diameter	15.75 mm
Material quality	1.4404
Operating pressure max	10 bar
Outer diameter	19.05 mm
Output	90 Mbar
Surface finish	$RA < 0,8/1,2 \mu m$
Temperature operational max	120 °C

<b>Temperature operational min</b>	0 °C
<b>Weight</b>	0.3 kg