

DEFINOX - DCX 3 & DCX 4 MINI

Manual & Pneumatic

DE-NU019A27100

DCX3 mini, 3/4" T-body, NC pneumatic, SS/PFA/FKM

- High packing pressure
- Independent and compact body
- Many configuration options
- Possible use on a wide range of applications



PRODUCT DESCRIPTION

Definox Mini Seat Valves.

This seat valve design offers a wide range of options and variants.

Technical advantages:

- From 1/2" to 1"
- Fitted with PEEK plug as standard - inert to chemical products
- Welded or Clamp ends possible
- Ergonomic handle with visual opening indicator
- Elastomer seal available for charged products
- High packing pressure
- Self-contained and compact body with a wide range of configuration options:
- Possible use on a wide range of applications
- Easy and fast maintenance thanks to the clamp assembly

TECHNICAL DATA

| | |
|-------------------------------|-----------------------------|
| Certificate | 3.1 EN10204 |
| Connection type | Weld ends |
| Description | STEEL PLUG |
| Housing | T Body |
| Housing | PFA/FKM |
| Inner diameter | 15.75 mm |
| Material quality | 1.4404 |
| Operating pressure max | 18 bar |
| Outer diameter | 19.05 mm |
| Surface finish | Indv.: RA 0,8µm Udv.: 1,2µm |

Temperature operational max 140 °C

Temperature operational min -5 °C

Weight 1.5 kg



Hus / Body:
L form

Hus / Body:
T form



Hus / Body:
L/L form

Hus / Body:
L/T form

Hus / Body:
T/L form



Hus / Body:
L/L form

Hus / Body:
L/T form

Hus / Body:
T/L form

