


DEFINOX - DCX 3 & DCX 4 MINI

Manual & Pneumatic

DE-NU019F34100

DCX3 mini, 3/4" X-body, Manual, SS/EPDM

- High packing pressure
- Independent and compact body
- Many configuration options
- Possible use on a wide range of applications



PRODUCT DESCRIPTION

Definox Mini Seat Valves.

This seat valve design offers a wide range of options and variants.

Technical advantages:

- From 1/2" to 1"
- Fitted with PEEK plug as standard - inert to chemical products
- Welded or Clamp ends possible
- Ergonomic handle with visual opening indicator
- Elastomer seal available for charged products
- High packing pressure
- Self-contained and compact body with a wide range of configuration options:
- Possible use on a wide range of applications
- Easy and fast maintenance thanks to the clamp assembly


TECHNICAL DATA

Certificate	3.1 EN10204
Connection type	Weld ends
Description	STEEL PLUG
Housing	X Body
Housing	EPDM
Inner diameter	15.75 mm
Material quality	1.4404
Operating pressure max	18 bar
Outer diameter	19.05 mm
Surface finish	Indv.: RA 0,8µm Udv.: 1,2µm

Temperature operational max 140 °C




Temperature operational min -5 °C

Weight 1.5 kg



Hus / Body:
L form


Hus / Body:
T form



Hus / Body:
L/L form

Hus / Body:
L/T form

Hus / Body:
T/L form



Hus / Body:
L/L form

Hus / Body:
L/T form

Hus / Body:
T/L form

