


## DEFINOX - DCX 3 & DCX 4 MINI

### Manual & Pneumatic

DE-MU012F12100

DCX4 mini, 1/2" L-L-body, Manual, PEEK/FKM

- High packing pressure
- Independent and compact body
- Many configuration options
- Possible use on a wide range of applications



### PRODUCT DESCRIPTION

Definox Mini Seat Valves.

This seat valve design offers a wide range of options and variants.

Technical advantages:

- From 1/2" to 1"
- Fitted with PEEK plug as standard - inert to chemical products
- Welded or Clamp ends possible
- Ergonomic handle with visual opening indicator
- Elastomer seal available for charged products
- High packing pressure
- Self-contained and compact body with a wide range of configuration options:
- Possible use on a wide range of applications
- Easy and fast maintenance thanks to the clamp assembly

### TECHNICAL DATA

|                        |                             |
|------------------------|-----------------------------|
| Certificate            | 3.1 EN10204                 |
| Connection type        | Weld ends                   |
| Description            | PEEK PLUG                   |
| Housing                | L+L Body                    |
| Housing                | FKM                         |
| Inner diameter         | 9.4 mm                      |
| Material quality       | 1.4404                      |
| Operating pressure max | 18 bar                      |
| Outer diameter         | 12.7 mm                     |
| Surface finish         | Indv.: RA 0,8µm Udv.: 1,2µm |



Hus / Body:  
L form

Hus / Body:  
T form



Hus / Body:  
L/L form

Hus / Body:  
L/T form

Hus / Body:  
T/L form



Hus / Body:  
L/L form

Hus / Body:  
L/T form

Hus / Body:  
T/L form

