OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

DEFINOX - DCX 3 TANK OUTLET

pneumatic

DE-ES025B11101
DCX3 Tankoutlet, Hoisting, Pneumatic, L-body, 1",
PFA/EPDM



- Leak tightness at high temperature and good resistance to chemical products
- Spherical body with large wall thickness ensures excellent resistance to expansion
- Can be used on a wide range of applications
- Complete interchangeability of sub-components
- Easy and fast maintenance thanks to the clamp assembly

PRODUCT DESCRIPTION

Definox DCX3 Tank outlet valve.
The ideal solution for Food, Brewery, Cosmetics, and Pharmaceutical processes.
The DCX3 is fitted as standard with a liquid PFA seal that ensures excellent cleaning of the valve.
Technical advantages:
· From DN 25 to DN 150
· Two versions: Raising or lowering plug
· PFA liquid seal, perfectly washable, ensures perfect leak tightness at high temperature and good resistance to chemical products
· Spherical body with thick walls ensures excellent resistance to expansion
· The plug can be supplied with an elastomer seal
· Pneumatic actuator, removable and easily adjustable: NO-NC-DE Double effect
· Possible use on a wide range of applications
· Complete interchangeability of sub-components
· Easy and fast maintenance thanks to the clamp assembly.

TECHNICAL DATA

Certificate	3.1 EN10204
Connection type	Weld ends
Description	Hoisting plug
Flange	Ø139mm
Function	Normally Closed
Housing	L-body
Housing	PFA/EPDM
Inner diameter	22.6 mm
Material quality	1.4404
Outer diameter	25 mm

Pressure max	7 bar
Surface finish	RA<0,8/1,2µm
Temperature range	-5°C/+140°C
Weight	4.5 kg



