

## DEFINOX - SAMPLING VALVE - MICRO & MINI

Manual and Pneumatic

DE-PD010A6C6100E

Micro valve 2 x 10/12 pipes, Pneumatic&manual, White EPDM

- SIP or CIP
- Simple and safe solution for sampling
- Compact pneumatic actuator
- Fast and easy membrane replacement
- 3.1 EN10204 - EHEDG



### PRODUCT DESCRIPTION

PEX Test outlet valve

Specifications:

- DN 6/8 - DN 16/18

Materials:

- Body: stainless steel 1.4404 / 316L machined from solid piece
- Handle: white plastic or stainless steel 1.4301 / 304
- Membrane: FKM (black / green with spot) - WMQ (white) - EPDM (black) - PFA / EPDM (white - hard)

Connections:

- Clamp - Micro Ø25.4 mm or Mini Ø33.9 mm

Controls:

- Manual - PEX - Ergonomic handle
- Pneumatic

Surface:

- RA exterior = 0.8 µm
- RA inside = 0.8 µm standard (0.4 µm on request)

Operating conditions:

- Max. temperature: + 120 ° C
- Min. temperature: 0 ° C
- Max. working pressure: 10 bar

### TECHNICAL DATA


|                 |                         |
|-----------------|-------------------------|
| Certificate     | 3.1 EN10204             |
| Connection type | Micro clamp             |
| Description     | Pneumatic + manual lift |
| Flange          | Ø25.4mm                 |
| Housing         | Aisi 316L/ 1.4404       |
| Housing         | White EPDM              |

Process connection


2 x 10/12 pipes

Surface finish


RA<0,8/1,2µm




Micro flange



Mini flange



Micro flange



Mini flange