OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

SLI INPUT RELAYS FOR MA LOADS AC CONTROL

SLI120CRP
I/P Plug-in Relay 120V ac 2-wire Proxy



- AC control / DC load
- Galvanic isloation 4kV, 8mm creep distance
- Effective interference elimination
- Compatible with both NPN and PNP logic
- LED indication

PRODUCT DESCRIPTION

The relays are used as an interface between AC sensors and control systems. The integrated interference protection provides reliable operation even in very demanding electrical environments. Thanks to interference protection, signal cables can be run alongside power cables on, for example, cable racks for more than 1.5 km without capacitive cross-talk affecting relays. The relays have no mechanical parts, which provides very reliable application. The CRP models are especially designed for connecting to 2-wire sensors that generate leakage current. The CRP relays are blind to leakage currents up to 3.5 mA.

TECHNICAL DATA

INPUT DATA

Input current max	8 mA
Power consumption	7 mA
Response time	20 ms
Release time	40 ms
Input voltage max	140
Switching voltage	80 V
Turn-off voltage	60 V
Input impedance, typ	17 kΩ
Input voltage nom	120

OUTPUT DATA

Number of poles	1
Load current	50 mA

Leakage current	1 µA
Load voltage dc max	60 V
Voltage drop over semiconductor at max	0.4 V
Voltage drop	0.2 V

GENERAL DATA

Width	12.5 mm
Temperature operational min	-25 °C
Temperature operational max	70 °C
Storage temperature min	-40 °C
Storage temperature max	70 °C
Material	PBT
Weight	40 g
Approvals	CE, UL







