

## SLO OUTPUT RELAYS FOR A LOADS

SLO120CRA

O/P Plug-in Relay 120V dc / 0-250V dc 1.8A

- DC control/dc load
- Galvanic isolation 4 kV, 8 mm creep distance
- Effective interference elimination
- Compatible with NPN/PNP logic
- LED indication



### PRODUCT DESCRIPTION

The relays are used as interfaces between control systems and DC loads. The relays handle inductive loads and high DC voltages with low load reduction compared to mechanical relays, which provide a long lifetime. If a diode is mounted across a load, such as 1N4007, the nominal current applies, even with high inductive loads. (Keep in mind that the drop-out time increases when mounting a diode.) The relays have no mechanical parts, which means very reliable application. The integrated interference protection provides reliable operation even in very demanding electrical environments. Thanks to interference protection, signal cables can be run alongside power cables on, for example, cable racks for more than 1.5 km without capacitive cross-talk affecting relays.

## TECHNICAL DATA

### INPUT DATA

Input current at nominal voltage, typ	3.5 mA
Input current max	4 mA
Response time	0.5 ms
Release time	0.5 ms
Control voltage dc min	95 V
Control voltage dc max	140 V
Switching voltage	80 V
Turn-off voltage	60 V
Input impedance, typ	34 kΩ
Input voltage nom	120

### OUTPUT DATA

Number of poles	1
Load current	1.8 A
Leakage current	1 mA
Peak current	12 A (10ms)
Load voltage dc max	250 V
Voltage drop	1 V

### GENERAL DATA

Width	12.5 mm
Temperature operational min	-25 °C
Temperature operational max	70 °C
Storage temperature min	-40 °C
Storage temperature max	70 °C
Colour	Red
Material	PBT
Weight	40 g
Approvals	CE, UL

