

## 1-DC SERIES RELAY

D1D40

Panel Mount SSR 100V dc 40A, 3.5-32V dc In, FET  
Output



- Load current 7A to 40A
- Operating voltage 100VDC to 500VDC
- Control voltage 3.5-32 VDC



### PRODUCT DESCRIPTION

With MOSFET output, this 1-DC Series Panel Mount DC Solid State Relay offers reliable fast switching of DC loads through low On-State resistance. Power ratings for this DC output SSR range up to 100 Amps at 100 VDC and 10 Amps at 500 VDC.

The 1-DC Series panel mount DC SSR also features:

- DC control input: 3.5-32 VDC
- Epoxy-free design which reduces internal stress
- EMC compliant to Level 3
- High PWM switching capability (up to 5 kHz on selected models)
- UL approved, CE compliant to EN60950-1
- Low-impedance MOSFET output minimizes total power dissipation
- Easily paralleled for high-current applications

## TECHNICAL DATA

### OVERVIEW

Output current	40 A
Output voltage	1-100V dc
Control voltage	3-32V dc
Connection	Screw connection
Additional features	N/A

### OUTPUT SPECIFICATION

Output voltage	1-100V dc
----------------	-----------

Number of poles	1
-----------------	---

## INPUT SPECIFICATION

Control voltage	3-32V dc
-----------------	----------

Input current min	10 mA
-------------------	-------

Input current max	15 mA
-------------------	-------

## GENERAL SPECIFICATION

Temperature operational min	-40 °C
-----------------------------	--------

Temperature operational max	100 °C
-----------------------------	--------

Storage temperature max	125 °C
-------------------------	--------

Storage temperature min	-40 °C
-------------------------	--------

Weight	75.5 g
--------	--------

Height	57.3 mm
--------	---------

Width	44.5 mm
-------	---------

Depth	22.6 mm
-------	---------

