

CKR60 SERIES

CKRA6030-10
DIN Rail SSR 22.5mm 660V ac 30A, 110-280V ac In,
Inst.

- Load current 10, 20, 30 A
- Operating voltage 48-660 VAC
- Control voltage 4-32 VDC, 110-280 VAC, 90-140 VAC, 18-36 VAC
- Broad range of control voltage



PRODUCT DESCRIPTION

Ratings from 10A to 30A @ 660 VAC - Slim 22.5mm (width) package - SCR output for heavy industrial loads - LED input status indicator - AC or DC control - zero voltage (resistive loads) or instantaneous turn on (inductive loads) output

- Rating from 10A to 30A @ 660VAC
- Slim 22.5mm (width) package
- SCR output for heavy industrial loads
- LED input status indicator
- AC or DC control
- Zero Voltage (resistive loads) or Instantaneous (inductive loads) turn-on output

TECHNICAL DATA

OVERVIEW

Output current	30 A
Output voltage	48-660V ac
Control voltage	110-280V ac
Connection	Screw connection
Type of control	Instantaneous turn on
Additional features	N/A

OUTPUT SPECIFICATION

Output voltage	48-660V ac
Number of poles	1

INPUT SPECIFICATION

Control voltage	110-280V ac
-----------------	-------------

GENERAL SPECIFICATION

Temperature operational min	-40 °C
-----------------------------	--------

