

## CKR60 SERIES

CKRB6020P  
 DIN Rail SSR 22.5mm 660V ac 20A, 90-140V ac In, ZC  
 IOP



- Load current 10, 20, 30 A
- Operating voltage 48-660 VAC
- Control voltage 4-32 VDC, 110-280 VAC, 90-140 VAC, 18-36 VAC
- Broad range of control voltage



### PRODUCT DESCRIPTION

Ratings from 10A to 30A @ 660 VAC - Slim 22.5mm (width) package - SCR output for heavy industrial loads - LED input status indicator - AC or DC control - zero voltage (resistive loads) or instantaneous turn on (inductive loads) output

- Rating from 10A to 30A @ 660VAC
- Slim 22.5mm (width) package
- SCR output for heavy industrial loads
- LED input status indicator
- AC or DC control
- Zero Voltage (resistive loads) or Instantaneous (inductive loads) turn-on output

## TECHNICAL DATA

### OVERVIEW

<b>Output current</b>	20 A
<b>Output voltage</b>	48-660V ac
<b>Control voltage</b>	90-140V ac
<b>Connection</b>	Screw connection
<b>Type of control</b>	Zero voltage turn on
<b>Additional features</b>	Overvoltage protection included

### OUTPUT SPECIFICATION

Output voltage	48-660V ac
Number of poles	1

## INPUT SPECIFICATION

Control voltage	90-140V ac
-----------------	------------

## GENERAL SPECIFICATION

Temperature operational min	-40 °C
Temperature operational max	80 °C
Storage temperature max	125 °C
Storage temperature min	-40 °C
Weight	280 g
Height	81.9 mm
Width	22.5 mm
Depth	99 mm

