OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

CKR60 SERIES

CKRD6010P
DIN Rail SSR 22.5mm 660V ac 10A, 4.5-32V dc In, ZC IOP



- Load current 10, 20, 30 A
- Operating voltage 48-660 VAC
- Control voltage 4-32 VDC, 110-280 VAC, 90-140 VAC, 18-36 VAC
- Broad range of control voltage

PRODUCT DESCRIPTION

Ratings from 10A to 30A @ 660 VAC - Slim 22.5mm (width) package - SCR output for heavy industrial loads - LED input status indicator - AC or DC control - zero voltage (resistive loads) or instantaneous turn on (inductive loads) output

- Rating from 10A to 30A @ 660VAC
- Slim 22.5mm (width) package
- SCR output for heavy industrial loads
- LED input status indicator
- AC or DC control
- Zero Voltage (resistive loads) or Instantaneous (inductive loads) turn-on output

TECHNICAL DATA

OVERVIEW

Output current	10 A
Output voltage	48-660V ac
Control voltage	4-32V dc
Connection	Screw connection
Type of control	Zero voltage turn on
Additional features	Overvoltage protection included

OUTPUT SPECIFICATION

Output voltage	48-660V ac
Number of poles	1

INPUT SPECIFICATION

Control voltage	4-32V dc

GENERAL SPECIFICATION

Temperature operational min	-40 °C

Temperature operational max	80 °C
Storage temperature max	125 °C
Storage temperature min	-40 °C
Weight	280 g
Height	81.9 mm
Width	22.5 mm
Depth	99 mm





