

1-DC SERIES RELAY

D4D12
 Panel Mount SSR 400V dc 12A, 3.5-32V dc In, FET
 Output



- Load current 7A to 40A
- Operating voltage 100VDC to 500VDC
- Control voltage 3.5-32 VDC



PRODUCT DESCRIPTION

With MOSFET output, this 1-DC Series Panel Mount DC Solid State Relay offers reliable fast switching of DC loads through low On-State resistance. Power ratings for this DC output SSR range up to 100 Amps at 100 VDC and 10 Amps at 500 VDC.

The 1-DC Series panel mount DC SSR also features:

- DC control input: 3.5-32 VDC
- Epoxy-free design which reduces internal stress
- EMC compliant to Level 3
- High PWM switching capability (up to 5 kHz on selected models)
- UL approved, CE compliant to EN60950-1
- Low-impedance MOSFET output minimizes total power dissipation
- Easily paralleled for high-current applications

TECHNICAL DATA

OVERVIEW

| | |
|---------------------|------------------|
| Output current | 12 A |
| Output voltage | 1-400V dc |
| Control voltage | 3-32V dc |
| Connection | Screw connection |
| Additional features | N/A |

OUTPUT SPECIFICATION

| | |
|----------------|-----------|
| Output voltage | 1-400V dc |
|----------------|-----------|

Number of poles 1

INPUT SPECIFICATION

| | |
|-------------------|----------|
| Control voltage | 3-32V dc |
| Input current min | 10 mA |
| Input current max | 15 mA |

GENERAL SPECIFICATION

| | |
|-----------------------------|---------|
| Temperature operational min | -40 °C |
| Temperature operational max | 100 °C |
| Storage temperature max | 125 °C |
| Storage temperature min | -40 °C |
| Weight | 75.5 g |
| Height | 57.3 mm |
| Width | 44.5 mm |
| Depth | 22.6 mm |

