

## CMR24 SERIES

CMRD2435  
 DIN Rail SSR 45mm 280V ac 35A, 3-32 V dc In, ZC



- Load current 35, 45, 55 and 65 A
- Operating voltage 280 VAC
- Control voltage 3-32 VDC and 90-140 VAC
- Broad range of load current

### PRODUCT DESCRIPTION

Ratings from 35A to 65A @ 280 VAC - 45mm (width) package - SCR output for heavy industrial loads - LED input status indicator - AC or DC control - zero voltage (resistive loads) or instantaneous turn on (inductive loads) output

- Ratings from 35A to 65A @ 280 VAC
- 45mm (width) package
- SCR output for heavy industrial loads
- LED input status indicator
- AC or DC control
- Zero-crossing (resistive loads) or random-fire (inductive loads) output

## TECHNICAL DATA

### OVERVIEW

Output current	35 A
Output voltage	24-280V ac
Control voltage	4-32V dc
Connection	Screw connection
Type of control	Zero voltage turn on
Additional features	N/A

### OUTPUT SPECIFICATION

Output voltage	24-280V ac
Number of poles	1

### INPUT SPECIFICATION

Control voltage	4-32V dc
-----------------	----------

### GENERAL SPECIFICATION

Temperature operational min	-40 °C
-----------------------------	--------

