

GNR SERIES 22.5MM RELAY

GNR10ACZ

DIN Rail SSR 22.5mm 240V ac 10A, 240V ac In, ZC



- Load current 10, 20 and 30A
- Operating voltage 24-280 VAC and 48-600 VAC
- Control voltage 4-32 VDC, 90-140 VAC and 180-280 VAC
- Broad range of power ratings



PRODUCT DESCRIPTION

These relays offer a broad range of power ratings which makes them suitable for diverse applications. Their high reliability and efficient design have made of them a market favorite for many years.

- Current ratings of 10, 20 and 30 amps
- Output voltage ratings: 24-280 and 48-600 VAC
- Direct Bond Copper (DBC) Substrate
- LED input status indicator
- UL 508 Endurance Rating for Enhanced Reliability
- UL/CSA/TUV Approved, CE Compliant
- Built-in overvoltage protection
- DIN Rail or Panel Mount
- Zero voltage or Instantaneous turn-on output

TECHNICAL DATA

OVERVIEW

Output current	10 A
Output voltage	24-280V ac
Control voltage	180-280V ac
Type of control	Zero voltage turn on
Activation	0 V
Additional features	Contactor configuration

OUTPUT SPECIFICATION

Output voltage	24-280V ac
----------------	------------

Peak current	190
Voltage drop over semiconductor at max	1.5 V
Number of poles	1
I ² t value	182 A ² s

INPUT SPECIFICATION

Control voltage	180-280V ac
Turn-off voltage	10 V
Input current min	6 mA
Input current max	20 mA
Response time	30 ms
Release time	20 ms

GENERAL SPECIFICATION

Insulation voltage in/out	2500 V
Temperature operational min	-20 °C
Temperature operational max	80 °C
Storage temperature max	100 °C
Storage temperature min	-40 °C
Weight	225 g
Height	89.8 mm
Width	22.5 mm
Depth	120.8 mm
LED indication	Input status indication
Approvals	CE, CSA, EMC, UL
IP class	IP20
Load voltage	AC

