OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

CROUZET - GN SERIES SOLID STATE RELAY

Panel Mount - AC Output Single Phase

84137011N
SSR 25A 24-280 VAC Out 20-265 VAC In ZC



- Zero cross or instantaneous switching
- Output current: 10 - 125 Amps
- Built-in over voltage protection (zero cross only)
- LED input status indicator

PRODUCT DESCRIPTION

TECHNICAL DATA

INPUT DATA

Control voltage	20-265V ac
Must turn-off voltage	5V ac/dc
LED input status indicator	Green
Input Current Max	10 mA
Input current min	5 mA AC / 4 mA DC
Minimum turn-on voltage	18V ac/dc


OUTPUT DATA


Number of poles	1
Type of control	Zero voltage turn on
Minimum Load Current	5 mA rms
Maximum Load Current	25 A rms
Maximum on-state voltage drop	1.23V
Maximum 1/2 Cycle $I^2 t$ for fusing (A^2 sec)	487/600
Maximum turn-off time (ms)	1/2 cycle
Maximum turn-on time (ms)	1/2 cycle
Maximum 1 cycle surge current	270/284 (min) 340 (typ)


Maximum off-state leakage current	1 mA rms
Transient Voltage	600 V pk
Minimum heat sink for rated current @ 40 °C	13 °C/W
1 Second surge current	100 A
Output voltage	24-280V ac
Output current	25 A
Thermal resistance junction to case	17 °C/W

GENERAL DATA


Mounting	Panel mount
Width	445 mm
Depth	291 mm
Height	594 mm
Approvals	CE, cRUus, VDE
Dielectric strength input to output (50/60Hz)	4000 V rms
Material base	Aluminium
Housing material	UL94 V-0
Ambient operating temperature	-40 ... +80°C
Ambient storage temperature	-40 ... +100°C
Weight	80 g









Input current vs Input Voltage
Standard Regulated AC inputs




GN front view



GN side view



GN



For the random (instantaneous) models, external overvoltage protection is recommended: TVS Diode

1 *Load*