

CROUZET - GN SERIES SOLID STATE RELAY

Panel Mount - AC Output Single Phase

84137321N
SSR 50A 48-660 VAC Out 90-260 VAC In Ins

- Zero cross or instantaneous switching
- Output current: 10 - 125 Amps
- Built-in over voltage protection (zero cross only)
- LED input status indicator



PRODUCT DESCRIPTION

TECHNICAL DATA

OVERVIEW

Output current	50 A
Output voltage	48-660V ac
Control voltage	90-260V ac
Mounting	Panel mount
Type of control	Instantaneous turn on

OUTPUT SPECIFICATION

Output voltage	48-660V ac
Maximum Load Current	50 A rms
Minimum Load Current	5 mA rms
Transient Voltage	1600 V pk
Maximum off-state leakage current	5 mA rms
1 Second surge current	230 A
Maximum 1 cycle surge current	700/_ (min) 750 (typ)
Maximum on-state voltage drop	1.37V
Thermal resistance junction to case	0.4 °C/W




Maximum 1/2 Cycle I ² t for fusing (A ² sec)	2450/2500
Minimum heat sink for rated current @ 40 °C	0.84 °C/W
Number of poles	1

INPUT SPECIFICATION





Control voltage	90-260V ac
Minimum turn-on voltage	90V ac
Must turn-off voltage	5V ac
Input current min	6.5 mA
Input Current Max	10 mA
Maximum turn-on time (ms)	<0.1
Maximum turn-off time (ms)	1/2 cycle

GENERAL SPECIFICATION

Dielectric strength input to output (50/60Hz)	4000 V rms
Ambient operating temperature	-40 ... +80°C
Ambient storage temperature	-40 ... +100°C
Weight	80 g
Height	59.4 mm
Width	44.5 mm
Depth	29.1 mm
Housing material	UL94 V-0
Material base	Aluminium
LED input status indicator	Green
Approvals	CE, cRUus, VDE



Input current vs Input Voltage
Standard Regulated AC inputs



For the random (instantaneous) models, external overvoltage protection is recommended: TVS Diode

1 Load