OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

CROUZET - GNA SERIES SOLID STATE RELAY

Panel Mount - AC Output Single Phase

84137480N
SSR 90A 48-660 VAC Out 4-32 VDC In ZC



- Zero cross switching
- Output current 25 - 90 Amps
- Cost effective solution
- LED input status indicator

PRODUCT DESCRIPTION

TECHNICAL DATA

OVERVIEW

Output current	90 A
Output voltage	48-660V ac
Control voltage	4-32V dc
Mounting	Panel mount
Type of control	Zero voltage turn on

OUTPUT SPECIFICATION

Output voltage	48-660V ac
Maximum Load Current	90 A rms
Minimum Load Current	5 mA rms
Transient Voltage	1200 V pk
Maximum off-state leakage current	1 mA rms
1 Second surge current	347
Maximum 1 cycle surge current	1100/_ (min) 1200 (typ)
Maximum on-state voltage drop	1.4V
Thermal resistance junction to case	0.3 °C/W
Maximum 1/2 Cycle I^2 t for fusing (A^2 sec)	7200


Minimum heat sink for rated current @ 40 °C	0.33 °C/W
Number of poles	1


INPUT SPECIFICATION


Control voltage	4-32V dc
Maximum reverse voltage	-32V dc
Minimum turn-on voltage	3.5V dc
Must turn-off voltage	2V dc
Input current min	10 mA
Input Current Max	14 mA
Maximum turn-on time (ms)	1/2 Cycle
Maximum turn-off time (ms)	1/2 Cycle

GENERAL SPECIFICATION


Dielectric strength input to output (50/60Hz)	4000 V rms
Ambient operating temperature	-40 ... +80°C
Ambient storage temperature	-40 ... +100°C
Weight	80 g
Height	59.4 mm
Width	44.5 mm
Depth	29.1 mm
Housing material	UL94 V-0
Material base	Aluminium
LED input status indicator	Green
Approvals	CE, cRUus, VDE









GNA Series DC control / Thyristor 40 A / 50 A / 90 A




GNA front view



GNA side view



GNA



Recomended overvoltage external protection: TVS Diode

1 *Load*