

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

### **TOUCH HMI**



Performance and Essential

88970564 HMI CTP107-E Performance 7"

- 4.3", 7" and 9.7" Resistive touch screens
- Direct connection to Crouzet Logic Controller
- RS232/485 & TCP/IP Ethernet Communications



#### **PRODUCT DESCRIPTION**

The Crouzet Touch range of HMI offers a high quality, high performance HMI but at a highly competative price.

We see more and more panels and system controlled and monitored by an HMI as opposed to traditional gauges, pilot light and meters. Modernising a panel with an HMI used to be an expensive and difficult task. Now, with the new range of Crouzet Touch HMI you can modernise and improve your application at a fraction of the historical costs.

The Crouzet Touch range consists of two versions,

ential	Performance
TFT-LCD resistive touch screen	TFT-LCD resistive touch screen
<ul> <li>Fan less cooling system</li> </ul>	<ul> <li>Fan less cooling system</li> </ul>
<ul> <li>32 bit 600 Mhz Cortex-A8 processor</li> </ul>	<ul> <li>32 bit 600Mhz or 1 Ghz Cortex-A8 processor</li> </ul>
Built-in RTC	Built-in RTC
Direct communication with Millenium 3 logic controller	<ul> <li>Direct communcation with Millenium 3 logic controller</li> </ul>
MODBUS RS232/485 protocol	<ul> <li>MODBUS RS232/485 protocol</li> </ul>
• CE Mark	MODBUS TCP/IP protocol
	<ul> <li>Integrated VNC server</li> </ul>
	<ul> <li>Additional function provided;</li> </ul>
	<ul> <li>Emails, recipe database, enhanced security and many more</li> </ul>
	CE mark, cULus listed

# **TECHNICAL DATA**

#### **GENERAL DATA**

Supply voltage	24 V DC
Display	7" TFT LCD
Current consumption	450 mA @24V
Resolution	800x480

Backlight	LED > 30.000 h
Processor	32 bit RISC Cortex-A8, 600 MHz
Memory for data	128 MB
I/O ports - COM port RS-232	COM1 male
I/O ports - COM port RS-485	COM1 2/4 wires male, COM3 2 wires male
I/O ports - ethernet port	1 x RJ45, 10/100 Mbit/s, MDI/MDIX
I/O ports - USB host	2.0

## OTHER TECHNICAL DATA

Width	200.4 mm
Depth	34 mm
Height	146.3 mm
Hole size	192 x 139 mm
IP class front	IP65
Temperature operational min	0°C
Temperature operational max	50 °C
Vibration resistance	10-25 Hz (X, Y, Z direction, 2G 30 minutes)
Approvals	UL, CE



