

TOUCH HMI

Performance and Essential

88970573

HMI CTP110-E Performance 10" + M3 Serial Cable

- 4.3", 7" and 9.7" Resistive touch screens
- Direct connection to Crouzet Logic Controller
- RS232/485 & TCP/IP Ethernet Communications



PRODUCT DESCRIPTION

The Crouzet Touch range of HMI offers a high quality, high performance HMI but at a highly competitive price.

We see more and more panels and system controlled and monitored by an HMI as opposed to traditional gauges, pilot light and meters. Modernising a panel with an HMI used to be an expensive and difficult task. Now, with the new range of Crouzet Touch HMI you can modernise and improve your application at a fraction of the historical costs.

The Crouzet Touch range consists of two versions,

Essential	Performance
<ul style="list-style-type: none"> • TFT-LCD resistive touch screen • Fan less cooling system • 32 bit 600 Mhz Cortex-A8 processor • Built-in RTC • Direct communication with Millenium 3 logic controller • MODBUS RS232/485 protocol • CE Mark 	<ul style="list-style-type: none"> • TFT-LCD resistive touch screen • Fan less cooling system • 32 bit 600Mhz or 1 Ghz Cortex-A8 processor • Built-in RTC • Direct communication with Millenium 3 logic controller • MODBUS RS232/485 protocol • MODBUS TCP/IP protocol • Integrated VNC server • Additional function provided; • Emails, recipe database, enhanced security and many more • CE mark, cULus listed

TECHNICAL DATA

GENERAL DATA

Supply voltage	24 V DC
Display	9,7" TFT LCD
Current consumption	650 mA @24V
Resolution	1024x768

Backlight	LED > 30.000 h
Processor	32 bit RISC Cortex-A8, 1 GHz
Memory for data	512 MB
I/O ports - COM port RS-232	COM1 male, COM3 male
I/O ports - COM port RS-485	COM2 2/4 wires female, COM3 2 wires female
I/O ports - ethernet port	2 x RJ45, 10/100/1000 Mbit/s, MDI/MDIX
I/O ports - USB host	2.0

OTHER TECHNICAL DATA

Width	260.6 mm
Depth	36.5 mm
Height	203.1 mm
Hole size	250 x 192 mm
IP class front	IP65
Temperature operational min	0 °C
Temperature operational max	50 °C
Vibration resistance	10-25 Hz (X, Y, Z direction, 2G 30 minutes)
Approvals	CE

