


OEM Automatic Ltd Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

PREPUNCHED COPPER BARS

BRP

BRP1015 BRP 80X5

- Length : 1750 mm
- Thickness : 5 mm and 10 mm
- Drilled with 10,5 mm diameter at 25 mm distance



PRODUCT DESCRIPTION

Teknomega have created a free to download software for calculating and selecting the most suitable busbar for your application. Find out more here.

Teknomegas pre-punched copper bars are the ideal products for instantaneous use. Pre-punched with 10.5mm diameter holes at a 25mm distance, also available in 5 and 10mm thickness. These busbars are mainly used in distribution bar cabinets. Having a range of copper bars with single or double predrilled holes, you save time in assembly and processing bars in the wiring of electrical equipment.

TECHNICAL DATA

GENERAL DATA

Cross section	400 mm ²	
Current at ΔT 50°C	1173 A	
DIMENSIONS		
Length	1750 mm	
Thickness	5 mm	
Width	80 mm	
Distance to hole centres	12.5 mm	
Hole diameter	10.5 mm	
Length between hole centres	25 mm	
AMPACITY		
Current at ΔT 30°C	885 A	
ADDITIONAL DATA		
Pack size	2	



