

OEM Automatic Ltd

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

PREPUNCHED COPPER BARS

BRP


BRP1020 BRP 100X5

• Length: 1750 mm

• Thickness: 5 mm and 10 mm

• Drilled with 10,5 mm diameter at 25 mm distance





PRODUCT DESCRIPTION

Teknomega have created a free to download software for calculating and selecting the most suitable busbar for your application. Find out more here.

Teknomegas pre-punched copper bars are the ideal products for instantaneous use. Pre-punched with 10.5mm diameter holes at a 25mm distance, also available in 5 and 10mm thickness. These busbars are mainly used in distribution bar cabinets. Having a range of copper bars with single or double pre-drilled holes, you save time in assembly and processing bars in the wiring of electrical equipment.

TECHNICAL DATA

GENERAL DATA

ADDITIONAL DATA

Pack size

| Cross section | 500 mm² | |
|-----------------------------|---------|--|
| Current at ΔT 50°C | 1431 A | |
| DIMENSIONS | | |
| Length | 1750 mm | |
| Thickness | 5 mm | |
| Width | 100 mm | |
| Distance to hole centres | 12.5 mm | |
| Hole diameter | 10.5 mm | |
| Length between hole centres | 25 mm | |
| AMPACITY | | |
| Current at ΔT 30°C | 1080 A | |

Weight 724 kg

