

ULTRAFLEXX ULTRA FLEXIBLE BUSBAR

Ultraflexx®

62851033

UFL 240-200-10, 240 mm² x 200 mm, ø10.5, 750 A

- CSA: 25mm² to 240mm²
- Rated current: up to 1200A with two parallel conductors
- Insulation: UL94 VO chlorine and fluorine free
- Voltage Rating - 1000VAC/1500VDC according to IEC 61439-1. 600VAC/750VDC According to UL
- Dielectric strength: 20kV/mm



PRODUCT DESCRIPTION

Ultraflexx® busbar has a very high flexibility and is vibration proof; this is due to the braided construction.

The conductor ends are press welded and pre-drilled, therefore no crimps or clamps are required and contact resistance is at a minimum.

This busbar is available in lengths of 100mm to 1000m as standard, with a current rating of up to 700A.
Custom lengths & hole sizes available on request.

The insulation used is halogen-free and flame retardant to UL224-VW1.

UL/CSA approved.

Voltage Rating - 1000VAC/1500VDC according to IEC 61439-1. 600VAC/750VDC According to UL

TECHNICAL DATA

GENERAL DATA

| | |
|---------------------|--------------------------|
| Colour | Black |
| Cross section | 240 mm ² |
| Current at ΔT 50°C | 745 A |
| Approvals | UL, CE, RoHS, EN50525 |
| Insulation material | Santoprene, halogen free |

DIMENSIONS

| | |
|-----------|--------|
| Length | 200 mm |
| Thickness | 8.9 mm |
| Width | 32 mm |

AMPACITY

| | |
|----------------------------|-------|
| Current at ΔT 30°C | 560 A |
|----------------------------|-------|

ADDITIONAL DATA

| | |
|---------------------|---------|
| Dielectric strength | 20 kV/m |
|---------------------|---------|

| | |
|---------------|--------|
| Hole diameter | 10.5mm |
|---------------|--------|

| | |
|--------|--------------|
| Weight | 0.5382276 kg |
|--------|--------------|