

ULTRAFLEXX ULTRA FLEXIBLE BUSBAR

Ultraflexx®

62858033

UFL 240-1000-10, 240 mm² x1000 mm, ø10.5, 750 A

- CSA: 25mm² to 240mm²
- Rated current: up to 1200A with two parallel conductors
- Insulation: UL94 VO chlorine and fluorine free
- Voltage Rating - 1000VAC/1500VDC according to IEC 61439-1. 600VAC/750VDC According to UL
- Dielectric strength: 20kV/mm



PRODUCT DESCRIPTION

Ultraflexx® busbar has a very high flexibility and is vibration proof; this is due to the braided construction.

The conductor ends are press welded and pre-drilled, therefore no crimps or clamps are required and contact resistance is at a minimum.

This busbar is available in lengths of 100mm to 1000m as standard, with a current rating of up to 700A.
Custom lengths & hole sizes available on request.

The insulation used is halogen-free and flame retardant to UL224-VW1.

UL/CSA approved.

Voltage Rating - 1000VAC/1500VDC according to IEC 61439-1. 600VAC/750VDC According to UL

TECHNICAL DATA

GENERAL DATA

Colour	Black
Cross section	240 mm ²
Current at ΔT 50°C	745 A
Approvals	UL, CE, RoHS, EN50525
Insulation material	Santoprene, halogen free

DIMENSIONS

Length	1000 mm
Thickness	8.9 mm
Width	32 mm

AMPACITY

Current at ΔT 30°C	560 A
----------------------------	-------

ADDITIONAL DATA

Dielectric strength	20 kV/m
---------------------	---------

Hole diameter	10.5mm
---------------	--------

Weight	2.4103236 kg
--------	--------------