
OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

ISOFLEXX LAMINATED BUSBAR

Isoflexx®

11311060
Classic, 4 x 15.5 x 0.8 - 267 A



- Material: CU 99.99999 pure
- Laminate thickness: 0.5mm to 1mm
- CSA: 22mm² to 1200mm²
- Rated current: 130A to 3725A
- Operating temperature: -50°C to 180°C

PRODUCT DESCRIPTION

Isoflexx® busbar can be bent into acute angles and has a small bending radius; this saves space in the enclosures.

Without the need for extra fixings, ISOFLEXX can be easily bolted to main busbars.

Available in lengths of 250mm to 2000mm as standard.

Isoflexx® busbar can also be customised, including cutting, bending and drilled/punched as required.

Insulation: high quality PVC or halogen free silicon

UL/CSA approved

Volatge Rating - 1000VAC/1500VDC according to IEC 61439-1. 600VAC/750VDC According to UL

.

TECHNICAL DATA

GENERAL DATA

Colour	Black
Cross section	49.6 mm²
Current at ΔT 50°C	267 A
Approvals	UL, CSA, CE, RoHS, EN50525
Insulation material	Self-closing rigid PVC

DIMENSIONS

Length	2000 mm
Thickness	0.8 mm
Width	16 mm

AMPACITY

Current at ΔT 30°C	201 A

ADDITIONAL DATA

Tinned	No
Number of laminates	4
Dielectric strength	20 kV/m

Weight	0.883 kg

