OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

MBS EARTH BRAIDS

336-150-33
MBS 50-150-10 Earth braid, 50 mm² x 150 mm, ø10.5, 250 A



- Available tinned or copper bare
- Press welded ends, no additional ferrules required
- Custom lengths and hole sizes available on request
- Quick and easy to install, no preparation required

PRODUCT DESCRIPTION

Earth braids from SPS, type MBS, are unique on the market as the ends of the braids are press welded under water in a special procedure.

The earth braids are produced of highly flexible E-Cu braids with a single wire dimension of 0.15mm, Cu bare or tinned.

The braids can be used as earth braids as well as highly flexible transmission elements, if connections with low transfer and connection resistance are needed.

Earth braids can be supplied with insulation. Other dimensions and cross sections up to 95mm² demand.

TECHNICAL DATA

GENERAL DATA

Cross section	50 mm²
Approvals	CE, RoHS, EN50525

DIMENSIONS

Length	150 mm
Thickness	3.2 mm
Width	25 mm
Hole diameter	10.5 mm

AMPACITY

Nominal current	250 A

ADDITIONAL DATA

Tinned	Yes

Weight	0.0675 kg