

MECHANICAL HYGROSTAT - KFR 012

KFR

01241.0-00

KFR 012 Hygrostat, Preset 50% RH, normally open

- Preset for humidity (65 % rF or 50 % rF)
- Compact
- High breaking capacity
- Simple mounting and quick installation

**PRODUCT DESCRIPTION**

This mechanical hygrostat KFR 012 is preset at 65 % or 50 %. This makes it easier to install hygrostats. It can often be difficult to know which humidity is to be set on the hygrostat. If the hygrostat is set at a value that is too low, the heating fan runs too frequently and thus produces large energy losses, or if the hygrostat is set at a value that is too high, components in the cabinet can be damaged. For the sake of simplicity, STEGO has developed two different models.

65 % humidity (rF) – for most cabinets with normal humidity

50 % humidity (rF) – for cabinets with components that are sensitive to high humidity.

TECHNICAL DATA**GENERAL DATA**

Control range humidity from	50 % RF
Control range humidity to	50 % RF
Hysteresis humidity	4% RH
Mounting	Clip on, DIN rail
Contact type	1 x N/O
Colour	Light grey

RATED OPERATING CONDITIONS

Breaking capacity	250VAC, 5 (0.2) A
Contact resistance	<10 mΩ
Connection type	2-pole terminal for 2.5mm ²
Operational temperature	0 °C ... +60°C
Storage temperature	-20°C ... +80°C

Life span	> 50,000 cycles
Humidity storage	<90% RH

DIMENSIONS

Height	60 mm
Depth	33 mm
Weight	0.04 kg
Material of body	Plastic

SAFETY & APPROVALS

IP class	IP20
Approvals	CE, UL, VDE
Flammability class	UL94-V0

EMC	EN 55014-1-2, EN 61000-3-2, EN 61000-3-3
-----	--



