

## DRAIN VALVE

DD 084

08410.0-00

DD 084 Drainage device, M50, 200ml/h, IP66 / IP67 / IP69K



- High enclosure class
- Good drainage capacity
- quick Mount
- Robust
- Weather and UV resistant

### PRODUCT DESCRIPTION

Condensation occurs in enclosures with high enclosure class when changing temperature. The use of a drain valve DD084 enables condensation to be removed without losing the maximum enclosure class.

The membrane structure prevents splashing of water from outside into the enclosure.

## TECHNICAL DATA

### GENERAL DATA

Flow of water at 5mm	200 ml/h
Mounting	M50 counternut

### DIMENSIONS

Height	49.5 mm
Behind panel depth	17.5 mm
Diameter	60 mm
Weight	0.06 kg

### MATERIAL

Colour	Grey
Degree of thickness	0,5 - 5,5 mm
Sealing gasket	NBR
Weatherization	UL746C (f1)

### RATED OPERATING CONDITIONS

Tightening torque nut	6
Tightening torque max	6
Operational temperature	-45°C ... +70°C

Storage temperature	-45°C ... +70°C
---------------------	-----------------

## SAFETY AND APPROVALS

Approvals	EAC, RoHS, UV - UL746C (f1)
IP class	IP66, IP67, IP69K

