

DRAIN VALVE

DD 084

08410.0-00

DD 084 Drainage device, M50, 200ml/h, IP66 / IP67 / IP69K

- High enclosure class
- Good drainage capacity
- quick Mount
- Robust
- Weather and UV resistant



PRODUCT DESCRIPTION

Condensation occurs in enclosures with high enclosure class when changing temperature. The use of a drain valve DD084 enables condensation to be removed without losing the maximum enclosure class.

The membrane structure prevents splashing of water from outside into the enclosure.

TECHNICAL DATA

GENERAL DATA

Flow of water at 5mm	200 ml/h
Mounting	M50 counternut

DIMENSIONS

Height	49.5 mm
Behind panel depth	17.5 mm
Diameter	60 mm
Weight	0.06 kg

MATERIAL

Colour	Grey
Degree of thickness	0,5 - 5,5 mm
Sealing gasket	NBR
Weatherization	UL746C (f1)

RATED OPERATING CONDITIONS

Tightening torque nut	6
-----------------------	---

Tightening torque max	6
Operational temperature	-45°C ... +70°C
Storage temperature	-45°C ... +70°C

SAFETY AND APPROVALS

Approvals	EAC, RoHS, UV - UL746C (f1)
IP class	IP66, IP67, IP69K

