OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

DATALOGIC QUICKSCAN I GBT/GM2400

QBT2430-BK
QuickScan QBT2430, BT, 2D kit, Black (Scanner, Charger)



- Detects 1D/2D code types
- Wide VGA 752 x 480 pixels image sensor
- 30,000+ reads per charge
- Interfaces: keyboard wedge, OEM (IBM) USB, RS-232, USB

PRODUCT DESCRIPTION

TECHNICAL DATA

1D Code types	Auto discriminates all standard 1D codes
2D Code Types	Aztec Code, China Han Xin Code, Data Matrix, MaxiCode, Micro QR Code, QR Code, Aztec Mesas
Additional features	Kit includes: Scanner and Base Station
Approvals	RoHS
Battery	Lithium-ion: 1400 mAh
Charge time	<4hrs @ 12VDC
Colour	Black
Dimension (mm)	163 x 91 x 41
Drop resistance	Withstands repeated drops from 5ft onto concrete surface
Humidity	5-95% (Non-condensing)
Immunity to ambient light	0 - 100,000 lux
Interface	Keyboard wedge, OEM (IBM) USB, RS-232, USB
IP class	IP42
Kit	Yes
Light source	Red LED 610-650 nm
Postal Code Types	China Post, IMB, KIX Post, Planet Code, Postnet, Royal Mail Code (RM4SCC), UK Postal, Australia Postal, Japan Postal, Canadian Post

Readable code types	1D / Linear Codes, 2D Codes, Postal Codes, Stacked Codes
Reading angle window	Pitch:+/-65°; Tilt: 360°; Skew: +/-60°
Reads per charge	30000
Sensor Type	Wide VGA: 752 x 480 pixels
Stacked Code Types	EAN/JAN Composites, GS1 Databar Composites, GS1 Databar Expanded Stacked, GS1 Databar Stacked, GS1 Databar Stacked Omnidirectional, Macro PDF, Micro PDF 417, PDF 417, UPC A/E Composites
Storage temperature max	70 °C
Storage temperature min	-40 °C
Temperature operational max	50 °C
Temperature operational min	0 °C
Weight	200 g
Wireless	Yes
Wireless technology	Bluetooth Wireless Communication