OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

DATALOGIC GRYPHON I GD4200

GD4290-BK
Gryphon I GD4290, Linear Imager, USB/RS-232/Wedge Multi-Interface, Black



- Detects all standard 1D codes
- Image sensor: CCD solid-state
- 1,000,000 pixels/sec
- Interfaces: USB type C, USB, RS-232, multi interface

PRODUCT DESCRIPTION

TECHNICAL DATA

1D Code types	Auto discriminates all standard 1D codes
Approvals	RoHS
Colour	Black
Dimension (mm)	166 x 68 x 109
Drop resistance	Withstands repeated drops from 6ft on concrete surface
Humidity	0-95% (Non-condensing)
Immunity to ambient light	0 - 130,000 lux
Interface	USB type C, USB, RS-232, Keyboard wedge multi interface
IP class	IP52
Kit	No
Light source	Dual LED array: 612 - 630nm
Output current	<350mA@5V, <150mA@12V
Readable code types	1D / Linear Codes
Reading angle window	Pitch:+/-65°; Tilt: +/- 45°; Skew: +/-65°
Reading speed	1,000,000 pixel/sec (400 reads/sec)
Sensor Type	CCD
Storage temperature max	70 °C
Storage temperature min	-40 °C
Temperature operational max	50 °C
Temperature operational min	0 °C
Weight	163 g

Wireless	No