

DATALOGIC GRYPHON I GD4200

GD4290-BK

Gryphon I GD4290, Linear Imager, USB/RS-232/Wedge Multi-Interface, Black



- Detects all standard 1D codes
- Image sensor: CCD solid-state
- 1,000,000 pixels/sec
- Interfaces: USB type C, USB, RS-232, multi interface

PRODUCT DESCRIPTION**TECHNICAL DATA**

| | |
|------------------------------------|---|
| 1D Code types | Auto discriminates all standard 1D codes |
| Approvals | RoHS |
| Colour | Black |
| Dimension (mm) | 166 x 68 x 109 |
| Drop resistance | Withstands repeated drops from 6ft on concrete surface |
| Humidity | 0-95% (Non-condensing) |
| Immunity to ambient light | 0 - 130,000 lux |
| Interface | USB type C, USB, RS-232, Keyboard wedge multi interface |
| IP class | IP52 |
| Kit | No |
| Light source | Dual LED array: 612 - 630nm |
| Output current | <350mA@5V, <150mA@12V |
| Readable code types | 1D / Linear Codes |
| Reading angle window | Pitch: +/-65°; Tilt: +/- 45°; Skew: +/-65° |
| Reading speed | 1,000,000 pixel/sec (400 reads/sec) |
| Sensor Type | CCD |
| Storage temperature max | 70 °C |
| Storage temperature min | -40 °C |
| Temperature operational max | 50 °C |
| Temperature operational min | 0 °C |
| Weight | 163 g |

Wireless

No
