
OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

DATALOGIC DE2X12 HALOGEN 2D MP

DE2X12-SR

- Maximum resolution DL/WA 6 mils, SR/MR 7.5 mils
- Humidity (Non-Condensing) 5 - 95%
- 21-pin ZIF connector
- Ambient light 0-100,000 lux



PRODUCT DESCRIPTION

TECHNICAL DATA

1D Code types	Auto discriminates all standard 1D codes
2D Code Types	Aztec Code, China Han Xin Code, Data Matrix, MaxiCode, Micro QR Code, QR Code
Approvals	RoHS
Dimension (mm)	11.4 x 21 x 15.75
Humidity	5 - 95% (Non-condensing)
Immunity to ambient light	0 - 100,000 lux
Interface	21-pin ZIF connector
Light source	Illumination: White LEDs
Postal Code Types	China Post, IMB, KIX Post, Planet Code, Postnet, Royal Mail Code (RM4SCC), Australia Postal, Japan Postal, Korea Post
Readable code types	1D / Linear Codes, 2D Codes, Postal Codes, Stacked Codes
Reading angle window	Pitch:+/-60°; Tilt: +/- 180°; Skew: +/-60°
Stacked Code Types	EAN/JAN Composites, GS1 Databar Composites, GS1 Databar Expanded Stacked, GS1 Databar Stacked, GS1 Databar Stacked Omnidirectional, Macro PDF, Micro PDF 417, PDF 417, UPC A/E Composites
Storage temperature max	70 °C
Storage temperature min	-40 °C

Temperature operational max	55 °C
Temperature operational min	-30 °C
Weight	9 g