

DATALOGIC POWERSCAN PM9600 SERIES

PM9600-SR910RBK20
PowerScan PM9600-SR, 910MHz, RS232
Kit(Cradle,Cable,Power Supply&Cord)

- Detects 1D and 2D code types
- Reads up to 2.5/3 mils 1D codes and 4/6 mils 2D codes
- 80,000 reads per charge
- Interfaces: RS-232, Keyboard wedge multi-interface, industrial and ethernet protocols



PRODUCT DESCRIPTION

TECHNICAL DATA

1D Code types	Auto discriminates all standard 1D codes
2D Code Types	Aztec Code, China Han Xin Code, Data Matrix, MaxiCode, Micro QR Code, QR Code, Dot Code
Approvals	RoHS
Charge time	3.2hrs @ 12VDC
Colour	Black/yellow
Dimension (mm)	19.8 x 14 x 7.9
Immunity to ambient light	0-100,000 lux
IP class	IP67, IP65
Kit	Yes
Postal Code Types	China Post, IMB, KIX Post, Planet Code, Postnet, Royal Mail Code (RM4SCC), Australia Postal, Japan Postal, Portuguese Post, Swedish Post
Readable code types	1D / Linear Codes, 2D Codes, Postal Codes, Stacked Codes, Digital Watermarking
Reads per charge	80000
Resolution	6 mils
Stacked Code Types	EAN/JAN Composites, GS1 Databar Composites, GS1 Databar Expanded Stacked, GS1 Databar Stacked, GS1 Databar Stacked Omnidirectional, Macro PDF, Micro PDF 417, PDF 417, UPC A/E Composites
Storage temperature max	70 °C
Storage temperature min	-40 °C

Temperature operational max	50 °C
Temperature operational min	-20 °C
Weight	425 g
Wireless	Yes