OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

POWER SOCKETS - SD 035

SD 035

03504.0-00
SD 035 USA/Canada Socket, with fuse, 6.3A, 125V



- Simple mounting with clips on DIN rail
- Quick connection with push clamps
- With or without fuse holder
- 9 Socket Variants

PRODUCT DESCRIPTION

The socket is easily mounted on 35 mm DIN rail and connected with screwless push clamps. Sockets are available for most countries and all with or without fuse holders.

TECHNICAL DATA

GENERAL DATA

Mounting	Clip on, DIN rail
Connection type	3 x pressure clamp
Socket	USA/CA
Nominal socket current	6.3 A
Fuse max	6.3 A

DIMENSIONS

Length	92 mm
Width	62 mm
Height	92 mm

SAFETY & APPROVALS

Protection class	I (earthed)
IP class	IP20
Approvals	cULus, RoHS, UL
Flammability class	UL94-V0

MATERIALS - CONDITIONS

Material plastic housing	Plastic
Colour	Light grey

Operational temperature	-45°C ... +70°C
Storage temperature	-45°C ... +70°C
Operating humidity	< 90% RH
Humidity storage	<90% RH

Voltage max	250 V ac
Weight	0.2 kg



