

OEM Automatic Ltd Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

## VARIOLINE LAMP - LED 021/022

Varioline

02210.0-30 LED 022 100-240 V AC, with PIR sensor, magnet fixing

- Maintenance free LED lighting
- IR sensor or switched versions
- 360° rotatable, glare free
- Screw or magnet fixing
- Ideal for large enclosures





#### PRODUCT DESCRIPTION

The LED 021/022 Varioline lamp is a compact and powerful LED lamp for enclosures, with a power consumption of only 11 W/16 W. The LED tube emits more than 1,000/1,700 Lm, illuminating even large enclosures to their full depth and height.

The emitted daylight colour of 6,500 K provides natural and non-fading colour reproduction and in-turn safety for the user. The LED 021/022 is glare free, rotatable 360° and uses Mid-power LEDs giving a service life of 60,000 h.

The range is easy to connect in series, supporting up to ten units. Connection plugs can either be purchased separately for own cable assembly or as a prewired 2 meter cable with VDE or UL approval as required.

# **TECHNICAL DATA**

### **GENERAL DATA**

Mounting	Magnetic mount
Nominal voltage	100-240 V AC
Activation	IR sensor
Connection type	2 pole plug with snap lock
Light source	LED
Luminance	1.080 Lm/1.730 Lm
Life span	60,000h at +20°C
DIMENSIONS	



600 mm

Width	44 mm
Height	44 mm

## **ELECTRICAL SPECIFICATION**


Frequency	50/60 Hz
Power consumption	16 W

#### **SAFETY & APPROVALS**


Protection class	II (double insulated)
IP class	IP20
Approvals	CE, RoHS
Approvals pending	UL, VDE

### **MATERIALS - CONDITIONS**

Material of body	Plastic
Colour	Translucent/White
Operational temperature	-30°C +40°C
Storage temperature	-40°C +85°C
Operating humidity	< 90% RH
Humidity storage	<90% RH
Voltage min	90 V ac
Voltage max	265 V ac
Weight	0.3 kg







LED 021 (Size 1) L1 = 400 mm L2 = 375 mm LED 022 (Size 2) L1 = 600 mm L2 = 575 mm View of magnet fixing

