

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

VARIOLINE LAMP WITH SOCKET LED 121/122 - OBSOLETE - NEW RANGE **COMING SOON**

Varioline

12215.0-30 OBSOLETE - LED 122 220-240V AC, PIR sensor, magnet fixing, Italy socket

- OBSOLETE
- FOR LED LIGHT USE LED 025
- FOR SOCKETS USE SD 035





PRODUCT DESCRIPTION

LED 121/122 Range is now Obsolete - Stego has a New Range coming Mid 2024

TECHNICAL DATA

GENERAL DATA

| Mounting | Magnetic mount |
|------------------------|----------------------------|
| Nominal voltage | 220-240 V AC |
| Activation | IR sensor |
| Connection type | 3-pole plug with snap lock |
| Socket | ΙΤ |
| Nominal socket current | 16 A |
| Light source | LED |
| Luminance | 1.080 Lm/1.730 Lm |
| Life span | 60,000h at +20°C |
| DIMENSIONS | |
| Length | 700 mm |

| Length | 700 mm |
|--------|--------|
| Width | 100 mm |
| Height | 44 mm |

ELECTRICAL SPECIFICATION


| Frequency | 50/60 Hz |
|-------------------|----------|
| Power consumption | 16 W |

SAFETY & APPROVALS

| Protection class | I (earthed) |
|-------------------|-------------|
| IP class | IP20 |
| Approvals | CE, RoHS |
| Approvals pending | VDE |

MATERIALS - CONDITIONS

| Material of body | Plastic |
|-------------------------|-------------------|
| Colour | Translucent/White |
| Operational temperature | -30°C +40°C |
| Storage temperature | -40°C +85°C |
| Operating humidity | < 90% RH |
| Humidity storage | <90% RH |
| | |
| Voltage min | 200 V ac |
| Voltage max | 265 V ac |
| Weight | 0.4 kg |



| | | _ |
|---|-----------|----------|
| ۴ | \square | 4 |

View of magnet fixing

| LED 121 (Size 1) | |
|------------------|--|
| L1 = 500 mm | |
| L2 = 475 mm | |

LED 122 (Size 2) L1 = 700 mm L2 = 675 mm

