

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

### VARIOLINE LAMP WITH SOCKET LED 121/122 - OBSOLETE - NEW RANGE **COMING SOON**

Varioline

12225.0-00 OBSOLETE - LED 122 220-240V AC, door switch, screw fixing, Italy socket

OBSOLETE

- FOR LED LIGHT USE LED 025
- FOR SOCKETS USE SD 035





#### **PRODUCT DESCRIPTION**

LED 121/122 Range is now Obsolete - Stego has a New Range coming Mid 2024

# **TECHNICAL DATA**

#### **GENERAL DATA**

Width

Height

| Mounting               | Screw fixing               |
|------------------------|----------------------------|
| Nominal voltage        | 220-240 V AC               |
| Activation             | Door switch                |
| Connection type        | 3-pole plug with snap lock |
| Socket                 | IT                         |
| Nominal socket current | 16 A                       |
| Light source           | LED                        |
| Luminance              | 1.080 Lm/1.730 Lm          |
| Life span              | 60,000h at +20°C           |
| DIMENSIONS             |                            |
| Length                 | 700 mm                     |

100 mm

44 mm

## **ELECTRICAL SPECIFICATION**


| Frequency         | 50/60 Hz |
|-------------------|----------|
| Power consumption | 16 W     |

### **SAFETY & APPROVALS**

| Protection class  | I (earthed) |
|-------------------|-------------|
| IP class          | IP20        |
| Approvals         | CE, RoHS    |
| Approvals pending | VDE         |


### **MATERIALS - CONDITIONS**

| Material of body        | Plastic           |
|-------------------------|-------------------|
| Colour                  | Translucent/White |
| Operational temperature | -30°C +40°C       |
| Storage temperature     | -40°C +85°C       |
| Operating humidity      | < 90% RH          |
| Humidity storage        | <90% RH           |
|                         |                   |
| Voltage min             | 200 V ac          |
| Voltage max             | 265 V ac          |
| Weight                  | 0.4 kg            |



L2 = 475 mm

L2 = 675 mm



View of screw fixing

