

ENCLOSURE LIGHTING - SL 025

SL 025

02521.0-03

SL 025 PIR, 230V ac, France/Poland socket, 16A

- ** SOME ITEMS OUT GOING RANGE **
- ** SEE OBSOLETE LIST IN DOWNLOADS **
- Integrated outlet
- Low energy fluorescent lamp



PRODUCT DESCRIPTION

The Slimline is designed to take as little vertical space as possible and thus be concealed behind the cabinet's upper front edge. The risk for glare is thus minimal despite the 11 W low energy lamp providing as much light as a 75 W light bulb. Slimline has an integrated outlet for, for example, a soldering iron or other device, and as standard has a screw-mounted push button switch. Both a magnetic bracket and IR sensor are available as options. If a magnetic bracket is chosen, installation is very simple and the lamp can be easily moved around in the cabinet to suit each situation. If you would also prefer an IR sensor, it only reacts when the door is opened, even if the door is transparent. Installation is facilitated even more in that a door switch is unnecessary.

TECHNICAL DATA

GENERAL DATA

| | |
|------------------------|-----------------------------|
| Mounting | Screw fixing |
| Nominal voltage | 230 V AC |
| Activation | IR sensor |
| Connection type | 3-pole terminal |
| Socket | FR/PL/CZ/SK |
| Nominal socket current | 16 A |
| Light source | Low energy Fluorescent lamp |
| Luminance | 900Lm |
| Life span | 10,000 Hrs |

DIMENSIONS

| | |
|--------|--------|
| Length | 345 mm |
|--------|--------|

| | |
|--------|--------|
| Width | 345 mm |
| Height | 40 mm |

ELECTRICAL SPECIFICATION

| | |
|-----------|----------|
| Frequency | 50/60 Hz |
|-----------|----------|

SAFETY & APPROVALS

| | |
|--------------------|------------------------|
| IP class | IP20 |
| Approvals | CE, EAC, GS, RoHS, VDE |
| Flammability class | UL94-V0 |

MATERIALS - CONDITIONS

| | |
|--------------------------|-----------------|
| Material plastic housing | Plastic |
| Colour | Light grey |
| Operational temperature | -20°C ... +50°C |
| Storage temperature | -45°C ... +70°C |
| Operating humidity | < 90% RH |
| Humidity storage | <90% RH |

| | |
|------------------------|--|
| Voltage min | 230 V ac |
| Voltage max | 230 V ac |
| Additional information | PIR sensor activates the light for 6 minutes |
| Weight | 0.4 kg |



Uttag 2
 Frankrike (FR), Polen (PL),
 Tjeckien (CZ), Slovakien (SK), etc.

