

ENCLOSURE LIGHTING LED 0255 MV RANGE

02550.0-00

LED 025MW 24-240V switch, magnetic/clip

- Multi-wide-range voltage (AC, DC)
- Durable and maintenance-free thanks to LED technology
- Daisy chain (up to 10 lights)
- On/off switch or motion detector
- Mounting kit for magnet, screw and clip fixing



PRODUCT DESCRIPTION

LED lights with Multi Wide Voltage are ideal for flexible use in enclosures and casings of different sizes. The Multi Wide Voltage supports both AC and DC voltages, ensuring maximum flexibility in the application. Fewer versions mean optimised processes in procurement and materials management. The mounting kit supplied also enables simple and versatile installation.

TECHNICAL DATA

GENERAL DATA

Mounting	Mounting brackets, Magnet
Nominal voltage	24-240 V AC/DC
Activation	Switch
Light source	LED

DIMENSIONS

Length	351 mm
Width	40 mm
Height	42 mm

ELECTRICAL SPECIFICATION

Power consumption	4.5 W
-------------------	-------

SAFETY & APPROVALS

Protection class	II (double insulated)
IP class	IP20
Approvals pending	CCC, EAC, UL E234324, VDE

MATERIALS - CONDITIONS

Material of body	Plastic
Colour	Transparent
Operational temperature	-40 °C...+60 °C
Storage temperature	-40 °C ...+85 °C
Operating humidity	< 90 % RH
Humidity storage	< 90 % RH

Voltage max	265 V
Weight	0.2 kg
Life span	60.000 h (+20 °C)

