

KES-E ECO FLEXIBLE PUSH-IN SQUARE CABLE ENTRY GROMMET

KES-E

28813.6

KES-E 18/24, Push fit cable entry, 18 cable, 1.5 - 2.5mm wall thickness



- For cable, pipe & hose diameters 1mm to 16.1mm
- IP54 Push in cable entry
- Halogen and Silicon free
- High density, up to 50 cables
- Ecolab approved

PRODUCT DESCRIPTION

The KES-E range from Contactclip offers a cost-effective solution for multiple cable, hose, pipe or tube entries in a confined space.

This system is ideal for applications where a high IP and strain relief is not required.

Designed for cables, tubes and pipes without connectors, the range offers between 12 and 50 entries with diameters of 1mm to 16.1mm.

The choice of two TPE frames can be quickly and easily mounted without the use of any tools into enclosures of 1.5mm to 2.5mm or 2.5mm to 4mm wall thickness enclosures.

In order to insert cables/tubes, the membrane (with marked centring point) must be pierced, now the cables can be easily guided through.

The TPE material ensures IP54 seal in a smooth hygienic design.

TECHNICAL DATA

GENERAL DATA

Type	KES-E
Mounting	Push in
Colour	Grey
IP class	IP54
Approvals	cUL, UL
NEMA class	12
Number of cables	18
Number of cables x cable diameter	5 x 1.0mm-10.5mm, 4 x 1.0mm-6.5mm, 5 x 1.0mm-12.5mm, 4 x 1.0mm-16.1mm
Length	142 mm
Width	44 mm

Installed height	5 mm
------------------	------

MOUNTING DETAILS

Wall thickness	1.5mm-2.5mm
Length of cutout	112 mm
Width of cutout	36 mm

MATERIALS

Material	TPE
Flammability class	V-0
Sealing material	TPE
Silicone-free	Yes
Halogen-free	Yes
Operating temperature from	-40 °C
Operating temperature to	90 °C

APPROVALS

Approvals	cUL, UL
UL test standard	UL 508A
cUL test standard	CSA C22.2 No. 14-18

ADDITIONAL DATA

Tariff code	39259020
Country of origin	DE
Weight	42.43 g
Pack size	10

