
OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

KDSI-SR INVERTED CABLE ENTRY SYSTEM

KDSI

28893.4
KDSI-SR 10/24, Inverted Screw frame kit including 28519.4 Inlay 6, 28518.4 Inlay 4, 28517.4 Inlay 2, no seals



- Easy assembly from the outside
- Four parts, many solutions
- uses the standard inlays and seals
- Perfect for pre-assembled cables, pipes and tubes
- High IP66 protection

PRODUCT DESCRIPTION

The inverted KDSI-SR screw frames enable a complete assembly from the outside. This is ideal for applications where space inside the panel is limited.
The KDSI-SR follow the same modular assembly principles as the popular KDS-SR, that and be assembled from the inside.
The changes to the inverted versions are the new mirrored geometry of the frame's opening tapers and an additional cover frame, which ensures the tight fit of the sealing elements towards the outside and maintains strain relief to DIN EN 62444
KDSI uses the same cut-outs as the standard Industrial Connector ranges from the manufacturers such as Harting, Walther and Ilme.

It also shares the same inlays and IP66 inserts as the KDS square and round variants.

TECHNICAL DATA

GENERAL DATA

Mounting	Screw on
Colour	Black
IP class	IP66
Approvals	cUL, UL, NEMA 4x, NEMA 12
Length	153 mm
Width	64 mm
Height	24.2 mm
Installed height	24.2 mm

MOUNTING DETAILS

Length of cutout	113.5 mm
Width of cutout	36 mm
Number of screw holes	4
Diameter of the screw holes	5.5 mm
Fixing screws	M5
Torque of the fixing screws	3

MATERIALS

Material	Polyamide 6.6
Glass-fibre reinforced	Yes
Flammability class	V-0
Sealing material	Polyurethane-based
Silicone-free	Yes
Halogen-free	Yes

Operating temperature from	-40 °C
Operating temperature to	120 °C


APPROVALS




Approvals	cUL, UL, NEMA 4x, NEMA 12
UL test standard	UL 508A
cUL test standard	C22.2 No. 14-18


ADDITIONAL DATA

Tariff code	39259020
Country of origin	DE
Weight	81.61 g
Pack size	1




min. 70
32
36
Ø 5,5
112
130



