

3 PHASE OVER/UNDER VOLTAGE RELAY H3US, H3USN

84873220

Voltage Monitor Relay H3US 3 x 220-480V

- Phase control of line voltage
- Wide range input voltage
- 35 mm cabinet with DIN rail
- LED indication



PRODUCT DESCRIPTION

Control relay for monitoring of 3-phase networks with neutral (H3USN) and without neutral (H3US). Adjustable switch at the front for adjustment of correct voltage in 3-phase networks. The switch's position is not registered until the operating voltage is switched on. If the switch position is changed during operation, all LEDs (LED indications) begin to flash but the unit will continue to function normally with the voltage that was set at the most recent power connection. Monitors under-voltage between the phases that can be set between -2 % and -20 % of U_n (measurement voltage) and over-voltage that can be set between 2 % and 20 % of U_n . Each limit (over-/under-voltage) has its own relay output (R1 Over and R2 Under) and there is an adjustable time delay for each relay output (Tt1 and Tt2), adjustable between 0.3-30 s. H3USN also checks for neutral interruption. Green LED (U_n) indicates supply voltage OK. Yellow LED (R) indicates active relay output.

TECHNICAL DATA

Approvals	CE, CSA, RoHS, UL
Breaking capacity	5A, 250V AC/DC
Function	Under/Overtoltage
IP class connection	IP20
IP class housing	IP30
Lower limit	-2 - -20%
Mounting	35 mm DIN-Rail
Output	2x Relay
Selection of rated voltage	220, 380, 400, 415, 440, 480V
Storage temperature max	70 °C
Storage temperature min	-40 °C

Supply voltage	3 x 220-480V AC
Temperature operational max	50 °C
Temperature operational min	-20 °C
Time delay startup	0.5 s
Time delay when exceeding the limit value	0,3-30s
Upper limit	2 - 20%
Weight	130 g

