


## INSULATED BOOTLACE FERRULES

2845.0X

H 2.5/14-D, 2.5 x 14mm Ferrule, Blue

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5...150 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated



### PRODUCT DESCRIPTION

If the individual strands at the ends of finely stranded wires need to be protected due to frequent connecting, then our CONTA-CLIP wire-end ferrules are an ideal solution. The ferrules must be crimped gas-tight with the ends of the wires. A simply distortion caused by the clamping force is not adequate. The wire-end ferrules can be crimped easily and securely with CONTA-CLIP crimping pliers. The resulting connections function properly both electrically and mechanically.

- Collar feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5-150 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated

## TECHNICAL DATA

### GENERAL DATA

|                                   |                          |
|-----------------------------------|--------------------------|
| Colour                            | Blue                     |
| Cross section max                 | 2.5 mm <sup>2</sup>      |
| Rated wire cross section to (AWG) | 14                       |
| Standard                          | German/UL (DIN) Standard |

### DIMENSIONS

|                     |         |
|---------------------|---------|
| Length              | 15 mm   |
| Length of tube      | 8 mm    |
| Stripping length    | 10 mm   |
| Thickness of collar | 0.25 mm |

|                    |         |
|--------------------|---------|
| Thickness of tube  | 0.15 mm |
| Diameter of collar | 4.2 mm  |
| Diameter of tube   | 2.2 mm  |

### MATERIALS

|                            |                            |
|----------------------------|----------------------------|
| Conductor tube             | Copper alloy               |
| Contact surface            | Galvanic tin-plated, shiny |
| Plastic collar             | Polypropylene-homopolymer  |
| Operating temperature from | -5 °C                      |
| Operating temperature to   | 105 °C                     |

### APPROVALS

|                  |     |
|------------------|-----|
| DIN 46228-4:1990 | Yes |
| DIN 46228-1:1992 | No  |

### ADDITIONAL DATA

|                   |          |
|-------------------|----------|
| Tariff code       | 85369010 |
| Country of origin | DE       |
| Weight            | 0.17 g   |
| Pack size         | 500      |

