

## INSULATED BOOTLACE FERRULES FOR DUAL CABLES

2796.0X

HZL 1.0-HL-D, 1.0 x 15mm, Dual Ferrule, Red

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5...150 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated



### PRODUCT DESCRIPTION

The special shape of the plastic collar makes it easy to feed in two wires in one wire-end ferrule.

## TECHNICAL DATA

### GENERAL DATA

Colour	Red
Cross section max	1 mm <sup>2</sup>
Rated wire cross section to (AWG)	17
Standard	UL (DIN)/French Standard

### DIMENSIONS

Length	19 mm
Length of tube	12 mm
Stripping length	16 mm
Thickness of collar	0.3 mm
Thickness of tube	0.15 mm
Diameter of tube	2 mm

### MATERIALS

Conductor tube	Copper alloy
----------------	--------------

Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

### APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

### ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0.18 g
Pack size	500

