


## INSULATED BOOTLACE FERRULES FOR DUAL CABLES

3008.0

HZL 0.75 L, 0.75 x 18mm, Dual Ferrule, White

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5...150 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated



### PRODUCT DESCRIPTION

The special shape of the plastic collar makes it easy to feed in two wires in one wire-end ferrule.

## TECHNICAL DATA

### GENERAL DATA

Colour	White
Cross section max	0.75 mm <sup>2</sup>
Rated wire cross section to (AWG)	18
Standard	German Standard

### DIMENSIONS

Length	24 mm
Length of tube	18 mm
Stripping length	21 mm
Thickness of collar	0.3 mm
Thickness of tube	0.15 mm
Diameter of tube	1.7 mm

### MATERIALS

Conductor tube	Copper alloy
----------------	--------------

<b>Contact surface</b>	Galvanic tin-plated, shiny
<b>Plastic collar</b>	Polypropylene-homopolymer
<b>Operating temperature from</b>	-5 °C
<b>Operating temperature to</b>	105 °C

## APPROVALS

<b>DIN 46228-4:1990</b>	Yes
<b>DIN 46228-1:1992</b>	No

## ADDITIONAL DATA

<b>Tariff code</b>	85369010
<b>Country of origin</b>	DE
<b>Weight</b>	0.22 g
<b>Pack size</b>	500

